

## MATERIAL SAFETY DATA SHEET

REVISION DATE: 04-18-2008

SUPERSEDES: 08-09-2005

### SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

#### COMPANY INFORMATION

Specialty Construction Brands, Inc.  
An H.B. Fuller Company  
1105 S. Frontenac Street  
Aurora, IL 60504  
Phone: 1-800-323-7407

Medical Emergency Phone Number (24 Hours): 1-888-853-1758  
Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

#### PRODUCT INFORMATION

PRODUCT IDENTIFIER: 801844PM  
PRODUCT NUMBER: CP0970  
PRODUCT NAME: CHILDERS CP-97  
PRODUCT DESCRIPTION: Adhesive

### SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

Unlisted ingredients are not 'hazardous' per the Occupational Safety and Health Administration Hazard Communication Standard (29 CFR 1910.1200) and/or are not found on the Canadian Workplace Hazardous Materials Information System ingredient disclosure list. See Section 8 for any additional exposure limit guidelines.

Chemical Name	CAS #	PERCENT	OSHA PEL
Sodium silicate	1344-09-8	30 - 50	Not established
Talc	14807-96-6	10 - 30	TWA (Respirable dust) 2 MG/M3
Aluminum silicate of potash and soda.	68476-25-5	5 - 10	TWA (as Al) (Total dust) 15 MG/M3 TWA (as Al) (Respirable dust) 5 MG/M3
Cellulose	9004-34-6	1 - 5	TWA (Total dust) 15 MG/M3 TWA (Respirable dust) 5 MG/M3
Crystalline silica	14808-60-7	1 - 5	TWA (Respirable dust) 0.1 MG/M3

### SECTION 3: HAZARDS IDENTIFICATION

#### EMERGENCY OVERVIEW

Corrosive to eye tissue.  
Causes severe skin irritation.  
Severe respiratory tract irritant.  
Harmful if swallowed.  
Cancer hazard.

HMIS RATING: HEALTH -- 3 FLAMMABILITY -- 0 REACTIVITY -- 0

## MATERIAL SAFETY DATA SHEET

---

See SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for personal protective equipment recommendations.

### POTENTIAL HEALTH EFFECTS BY ROUTE OF ENTRY

**EYE:** Corrosive to eye tissue. Can cause severe irritation, tearing, and burns that can quickly lead to permanent injury including blindness.

**SKIN:** Contact causes severe skin irritation and possible burns.

**INHALATION:** Can cause severe respiratory irritation, nausea, and headache. Inhalation of dusts produced during cutting, grinding or sanding of this product may cause irritation of the respiratory tract.

Overexposure to crystalline silica may cause silicosis.

This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur.

**INGESTION:** Ingestion is not an anticipated route of exposure. Harmful if swallowed. Corrosive to tissue. Can cause severe and permanent damage to mouth, throat, stomach. Aspiration may lead to lung damage.

### LONG-TERM (CHRONIC) HEALTH EFFECTS

**TARGET ORGAN(S):** Lungs

### REGULATED CARCINOGEN STATUS:

Unless noted below, this product does not contain regulated levels of NTP, IARC, ACGIH, or OSHA listed carcinogens.

Crystalline silica

**EXISTING HEALTH CONDITIONS AFFECTED BY EXPOSURE:** Lung disease

## SECTION 4: FIRST AID MEASURES

---

**IF IN EYES:** Immediately flush eyes with plenty of water for at least 20 minutes retracting eyelids often. This corrosive material can cause immediate and permanent eye damage. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention and monitor the eye daily as advised by your physician.

**IF ON SKIN:** Wash with soap and water. Remove contaminated clothing, launder immediately, and discard contaminated leather goods. Get medical attention immediately.

**IF VAPORS INHALED:** Remove to fresh air. Restore breathing, if necessary. Keep warm and quiet. Call a physician.

**IF SWALLOWED:** Corrosive. Do not induce vomiting! Drink one glass of water followed by milk if available. Seek medical attention immediately. Do not give anything by mouth to an unconscious person. Induced vomiting may lead to aspiration of the material into the lungs potentially causing chemical pneumonitis that may be fatal.

## SECTION 5: FIRE FIGHTING MEASURES

---

<b>FLASH POINT:</b>	Non flammable
<b>AUTOIGNITION TEMPERATURE:</b>	Not established
<b>LOWER EXPLOSIVE LIMIT (% in air):</b>	Not established
<b>UPPER EXPLOSIVE LIMIT (% in air):</b>	Not established
<b>EXTINGUISHING MEDIA:</b>	Use water spray, foam, dry chemical or carbon dioxide.
<b>UNUSUAL FIRE AND EXPLOSION HAZARDS:</b>	There is a possibility of pressure buildup in closed containers when heated. Water spray may be used to cool the containers.
<b>SPECIAL FIRE FIGHTING INSTRUCTIONS:</b>	Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment.
<b>HAZARDOUS COMBUSTION PRODUCTS:</b>	Carbon dioxide, Carbon monoxide

## MATERIAL SAFETY DATA SHEET

### SECTION 6: ACCIDENTAL RELEASE MEASURES

**SPECIAL PROTECTION:** Exposure to the spilled material may be severely irritating or toxic. Follow personal protective equipment recommendations found in Section 8 of this MSDS. Personal protective equipment needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, and the area in which the spill occurred. Never exceed any occupational exposure limits.

**CLEAN-UP:** Dike if necessary, contain spill with inert absorbent and transfer to containers for disposal. Keep spilled product out of sewers, watersheds, or water systems.  
Contain spill, dilute if necessary and neutralize. Remove with inert absorbent.

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

### SECTION 7: HANDLING AND STORAGE

**Handling:** Toxic or severely irritating material. Avoid contacting and avoid breathing the material. Use only in a well ventilated area. Aluminum is not an acceptable material of construction for pumps, mixers, fittings or storage for this product.

**Storage:** Store in a cool, dry place.

Consult the Technical Data Sheet for specific storage instructions.

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

**EYE PROTECTION:** Wear chemical splash goggles when handling this product. Additionally, wear a face shield when the possibility of splashing of liquid exists. Do not wear contact lenses. Have an eye wash station available.

**SKIN PROTECTION:** Prevent contact with this product. Wear chemically resistant gloves, long sleeved shirt, an apron, and other protective equipment depending on conditions of use.

**GLOVES:** Butyl rubber

**RESPIRATORY PROTECTION:** Respiratory protection will be required when ventilation or other engineering controls can not reduce the exposure to acceptable levels. NIOSH approved air purifying respirator with dust/mist filter if product is sprayed.  
Respirators should be selected by and used following requirements found in OSHA's respirator standard (29 CFR 1910.134).

**VENTILATION:** Local exhaust ventilation or other engineering controls are normally required when handling or using this product to avoid overexposure.

#### EXPOSURE LIMITS:

Chemical Name	ACGIH EXPOSURE LIMITS	AIHA WEEL
Sodium silicate	Not established	Not established
Talc	TWA (Respirable dust) 2 MG/M3	Not established
Aluminum silicate of potash and soda.	TWA (as Al) (Total dust) 10 MG/M3	Not established

**MATERIAL SAFETY DATA SHEET**

Cellulose	TWA (Total dust) 10 MG/M3	Not established
Crystalline silica	TWA (Respirable dust) 0.025 MG/M3	Not established

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

PHYSICAL STATE:	Liquid
COLOR:	Gray
ODOR:	Neutral
ODOR THRESHOLD:	Not established
WEIGHT PER GALLON (lbs.):	13.1
SPECIFIC GRAVITY:	1.57
SOLIDS (% by weight):	59.0
pH:	Not established
BOILING POINT (deg. C):	Not established
FREEZING/MELTING POINT (deg. C):	Not established
VAPOR PRESSURE (mm Hg):	Not established
VAPOR DENSITY:	Not established
EVAPORATION RATE:	Not established
OCTANOL/WATER COEFFICIENT:	Not established

**SECTION 10: STABILITY AND REACTIVITY**

STABILITY:	Stable under normal conditions.
CHEMICAL INCOMPATIBILITY:	Aluminum alloys
HAZARDOUS POLYMERIZATION:	Will not occur.
HAZARDOUS DECOMPOSITION PRODUCTS:	Carbon monoxide, carbon dioxide

**SECTION 11: TOXICOLOGICAL INFORMATION**

CHEMICAL NAME	LD50/LC50
Sodium silicate	Oral LD50 Rat = 1.1 g/kg
Talc	Not established
Aluminum silicate of potash and soda.	Not established
Cellulose	Oral LD50 Rat > 5 g/kg Inhalation LC50 Rat > 5800 mg/cu m/4H Dermal LD50 Rabbit > 2 g/kg
Crystalline silica	Not established

TOXICOLOGY SUMMARY: No additional health information available.

**SECTION 12: ECOLOGICAL INFORMATION**

OVERVIEW: No ecological information available

## MATERIAL SAFETY DATA SHEET

### SECTION 13: DISPOSAL CONSIDERATIONS

To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Solidify and dispose of in an approved landfill. Consult state, local or provincial authorities for more restrictive requirements.

### SECTION 14: TRANSPORTATION INFORMATION

Consult Bill of Lading for transportation information.

DOT: NOT REGULATED ,,,

### SECTION 15: REGULATORY INFORMATION

#### INVENTORY STATUS

U.S. EPA TSCA: This product is in compliance with the Toxic Substances Control Act's Inventory requirements.

CANADIAN CEPA DSL: This product is in compliance with the Canadian Domestic Substance List requirements.

If you need more information about the inventory status of this product call 651-236-5858.

This product may contain chemical substances that are regulated for export by various government agencies (such as the Environmental Protection Agency, the Bureau of Industry and Security, or the Drug Enforcement Administration, among others). Before exporting this product from the USA or Canada, we recommend you contact us at 651-236-5858 (USA) or 450-655-1306 x227 (Canada) to request an export review.

#### FEDERAL REPORTING

EPA SARA Title III Section 313

Unless listed below, this product does not contain toxic chemical(s) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR part 372. EPA has advised that when a percentage range is listed the midpoint may be used to fulfill reporting obligations.

Chemical Name	CAS#	%
---------------	------	---

WHMIS STATUS: Unless listed below, this product is not controlled under the Canadian Workplace Hazardous Materials Information System.

D2B D2A

E

#### STATE REPORTING

This MSDS is not prepared for distribution in California.

### SECTION 16: ADDITIONAL INFORMATION

This Material Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

Prepared by: The Global Regulatory Department

Phone: 651-236-5842

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to Specialty Construction Brands, Inc. from its suppliers, and because Specialty Construction Brands, Inc. has no control over the conditions of handling and use, Specialty Construction Brands, Inc. makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and Specialty Construction Brands, Inc. assumes no responsibility for use or reliance thereon. It is the responsibility of

## **MATERIAL SAFETY DATA SHEET**

---

the user of Specialty Construction Brands, Inc. products to comply with all applicable federal, state and local laws and regulations.