

MATERIAL SAFETY DATA SHEET

REVISION DATE: 12-20-2007

SUPERSEDES: 09-05-2007

SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

COMPANY INFORMATION

Specialty Construction Brands, Inc.
An H.B. Fuller Company
1105 S. Frontenac Street
Aurora, IL 60504
Phone: 1-800-323-7407

Medical Emergency Phone Number (24 Hours): 1-888-853-1758
Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

PRODUCT INFORMATION

PRODUCT IDENTIFIER: 802432PM
PRODUCT NUMBER: FD9066B
PRODUCT NAME: FOSTER 90-66 B
PRODUCT DESCRIPTION: Adhesive/Coating

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

Unlisted ingredients are not 'hazardous' per the Occupational Safety and Health Administration Hazard Communication Standard (29 CFR 1910.1200) and/or are not found on the Canadian Workplace Hazardous Materials Information System ingredient disclosure list. See Section 8 for any additional exposure limit guidelines.

Chemical Name	CAS #	PERCENT	OSHA PEL
Carbon black	1333-86-4	30 - 50	TWA 3.5MG/M3
Aromatic petroleum distillate	64742-95-6	10 - 30	Not established
Toluene	108-88-3	5 - 10	TWA 100ppm STEL 150ppm
Trimethylbenzene, 1,2,4-	95-63-6	5 - 10	Not established
Manganese compounds	1313-13-9	5 - 10	TWA (as Mn) Fume 1MG/M3 Ceiling (as Mn) 5MG/M3 STEL (as Mn) Fume 3MG/M3
Hydrogenated terphenyls	61788-32-7	1 - 5	TWA 0.5ppm
Terphenyls	26140-60-3	1 - 5	Ceiling 5MG/M3
Ethylbenzene	100-41-4	0.1 - 1	TWA 100ppm STEL 125ppm
Xylene	1330-20-7	0.1 - 1	TWA 100ppm

MATERIAL SAFETY DATA SHEET

			STEL 150ppm
--	--	--	-------------

SECTION 3: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Flammable

Moderate to severe eye irritant.

Causes skin irritation.

Moderate respiratory tract irritant.

Harmful if swallowed.

HMS RATING: HEALTH -- 2 FLAMMABILITY -- 3 REACTIVITY -- 0

See SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for personal protective equipment recommendations.

POTENTIAL HEALTH EFFECTS BY ROUTE OF ENTRY

EYE: Eye contact may cause moderate to severe eye irritation. Eye contact may result in tearing and reddening, but not likely to permanently injure eye tissue. Temporary vision impairment (cloudy or blurred vision) is possible.

SKIN: Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.

INHALATION: Can cause moderate respiratory irritation. Inhalation of dusts produced during cutting, grinding or sanding of this product may cause irritation of the respiratory tract.

Inhalation of high concentrations may result in central nervous system (CNS) effects such as dizziness, weakness, fatigue, nausea, headache, and lack of coordination. Overexposure to manganese compounds may cause manganese poisoning.

This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur.

INGESTION: Ingestion is not an anticipated route of exposure. Harmful if swallowed. Irritating to mouth, throat, and stomach.

LONG-TERM (CHRONIC) HEALTH EFFECTS

REPRODUCTIVE: Contains a substance that is a probable reproductive hazard based on human studies.

TARGET ORGAN(S): Lungs Reproductive system Liver Central nervous system Blood Kidneys Hemato System

REGULATED CARCINOGEN STATUS:

Unless noted below, this product does not contain regulated levels of NTP, IARC, ACGIH, or OSHA listed carcinogens.

Carbon black

Ethylbenzene

EXISTING HEALTH CONDITIONS AFFECTED BY EXPOSURE: Lung disease; Liver disease; Blood disorders (like anemia); Kidney disease

SECTION 4: FIRST AID MEASURES

IF IN EYES: Immediately flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention and monitor the eye daily as advised by your physician.

IF ON SKIN: Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.

MATERIAL SAFETY DATA SHEET

IF VAPORS INHALED: Remove to fresh air. Restore breathing, if necessary. Call a physician if symptoms persist.

IF SWALLOWED: Do not induce vomiting. Seek medical attention immediately. Drink two glasses of water or milk to dilute. Do not give anything by mouth to an unconscious person. Induced vomiting may lead to aspiration of the material into the lungs potentially causing chemical pneumonitis that may be fatal.

SECTION 5: FIRE FIGHTING MEASURES

FLASH POINT:	27C; 81F TCC
AUTOIGNITION TEMPERATURE:	Not established
LOWER EXPLOSIVE LIMIT (% in air):	Not established
UPPER EXPLOSIVE LIMIT (% in air):	Not established
EXTINGUISHING MEDIA:	Use water spray, foam, dry chemical or carbon dioxide.
UNUSUAL FIRE AND EXPLOSION HAZARDS:	Vapors are heavier than air and can travel to a source of ignition and flash back.
SPECIAL FIRE FIGHTING INSTRUCTIONS:	Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment.
HAZARDOUS COMBUSTION PRODUCTS:	Carbon dioxide, Carbon monoxide Manganese dioxide

SECTION 6: ACCIDENTAL RELEASE MEASURES

SPECIAL PROTECTION:	Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section 8 of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Evaporation of volatile substances can lead to the displacement of air creating an environment that can cause asphyxiation.
CLEAN-UP:	Dike if necessary, contain spill with inert absorbent and transfer to containers for disposal. Keep spilled product out of sewers, watersheds, or water systems. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area.

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

SECTION 7: HANDLING AND STORAGE

Handling:	Harmful or irritating material. Avoid contacting and avoid breathing the material. Use only in a well ventilated area. Keep away from heat, sparks and flame. Wash thoroughly after handling. Keep container closed. Emptied container retains vapor and product residue. Observe all labeled precautions until container is cleaned. Drums of this material should be grounded when pouring. DO NOT CUT OR WELD ON OR NEAR THIS CONTAINER.
Storage:	Store in a cool, dry, ventilated location. Keep away from heat, sparks, flame and other sources of ignition. Keep container closed.

Consult the Technical Data Sheet for specific storage instructions.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE PROTECTION:	Wear safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles
-----------------	---

MATERIAL SAFETY DATA SHEET

and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Have an eye wash station available.

SKIN PROTECTION:

Avoid skin contact by wearing chemically resistant gloves and long sleeved shirt. An apron may be appropriate if splashing can occur. Skin absorption may potentially contribute to the overall exposure to this material. Appropriate measures should be taken to prevent absorption so that the TLV is not invalidated.

GLOVES:

Nitrile

RESPIRATORY PROTECTION:

Respiratory protection may be required to avoid overexposure when handling this product. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. NIOSH approved air purifying respirator with organic vapor cartridge. Respirators should be selected by and used following requirements found in OSHA's respirator standard (29 CFR 1910.134).

VENTILATION:

Use local exhaust ventilation or other engineering controls to minimize exposures.

EXPOSURE LIMITS:

Chemical Name	ACGIH EXPOSURE LIMITS	AIHA WEEL
Carbon black	TWA 3.5MG/M3	Not established
Aromatic petroleum distillate	Not established	Not established
Toluene	TWA 20ppm	Not established
Trimethylbenzene, 1,2,4-	Not established	Not established
Manganese compounds	TWA (as Mn) 0.2MG/M3	Not established
Hydrogenated terphenyls	TWA 0.5ppm	Not established
Terphenyls	Ceiling 5MG/M3	Not established
Ethylbenzene	TWA 100ppm STEL 125ppm	Not established
Xylene	TWA 100ppm STEL 150ppm	Not established

MATERIAL SAFETY DATA SHEET**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

PHYSICAL STATE:	Liquid
COLOR:	Black
ODOR:	Solvent
ODOR THRESHOLD:	Not established
WEIGHT PER GALLON (lbs.):	9.6
SPECIFIC GRAVITY:	1.15
SOLIDS (% by weight):	75.0
pH:	Not established
BOILING POINT (deg. C):	Not established
FREEZING/MELTING POINT (deg. C):	Not established
VAPOR PRESSURE (mm Hg):	Not established
VAPOR DENSITY:	Not established
EVAPORATION RATE:	Not established
OCTANOL/WATER COEFFICIENT:	Not established

SECTION 10: STABILITY AND REACTIVITY

STABILITY:	Stable under normal conditions.
CONDITIONS TO AVOID:	Oxidizing conditions. Contamination
CHEMICAL INCOMPATIBILITY:	Not established
HAZARDOUS POLYMERIZATION:	Will not occur.
HAZARDOUS DECOMPOSITION PRODUCTS:	Carbon monoxide, carbon dioxide Manganese dioxide

SECTION 11: TOXICOLOGICAL INFORMATION

CHEMICAL NAME	LD50/LC50
Carbon black	Oral LD50 Rat > 15400mg/kg Dermal LD50 Rabbit > 3g/kg
Aromatic petroleum distillate	Oral LD50 Rat = 8400mg/kg
Toluene	Oral LD50 Rat = 636mg/kg Inhalation LC50 Rat = 49000mg/cu m/4H Dermal LD50 Rabbit = 14.1ml/kg
Trimethylbenzene, 1,2,4-	Oral LD50 Rat = 5g/kg Inhalation LC50 Rat = 18000mg/cu m/4H
Manganese compounds	Oral LD50 Rat = 3478mg/kg
Hydrogenated terphenyls	Oral LD50 Rat = 17500mg/kg
Terphenyls	Oral LD50 Mouse = 13200mg/kg
Ethylbenzene	Oral LD50 Rat = 3500mg/kg Dermal LD50 Rabbit = 17.8ml/kg
Xylene	Oral LD50 Rat = 4300mg/kg Inhalation LC50 Rat = 5000ppm/4H Dermal LD50 Rat = 1700mg/kg

TOXICOLOGY SUMMARY: No additional health information available.

MATERIAL SAFETY DATA SHEET

SECTION 12: ECOLOGICAL INFORMATION

OVERVIEW: No ecological information available

286 g VOC/liter of material, less water and exempt solvents
(VOC theoretically determined using EPA Reference method 24)

SECTION 13: DISPOSAL CONSIDERATIONS

This product meets the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. It is ignitable waste class D001. Disposal via incineration is recommended. Consult your state, local, or provincial authorities for more restrictive requirements.

LAND DISPOSAL RESTRICTIONS: Toluene Ethyl benzene Xylenes (o-, m-, p- isomers)

SECTION 14: TRANSPORTATION INFORMATION

Consult Bill of Lading for transportation information.

DOT: UN1133, ADHESIVES, 3, III
IATA: UN1133, ADHESIVES, 3, III

SECTION 15: REGULATORY INFORMATION

INVENTORY STATUS

U.S. EPA TSCA: This product is in compliance with the Toxic Substances Control Act's Inventory requirements.

EUROPEAN EINECS: This product is in compliance with the European Inventory of Notified and Existing Chemical Substances requirements.

AUSTRALIA AICS: This product is in compliance with the Australian Inventory of Chemical Substances requirements.

KOREAN TCCL: This product is in compliance with the Korean Existing Chemicals List requirements.

PHILIPPINES: This product is in compliance with the Philippine Inventory of Chemicals and Chemical Substances requirements.

If you need more information about the inventory status of this product call 651-236-5858.

This product may contain chemical substances that are regulated for export by various government agencies (such as the Environmental Protection Agency, the Bureau of Industry and Security, or the Drug Enforcement Administration, among others). Before exporting this product from the USA or Canada, we recommend you contact us at 651-236-5858 (USA) or 450-655-1306 x227 (Canada) to request an export review.

FEDERAL REPORTING

EPA SARA Title III Section 313

Unless listed below, this product does not contain toxic chemical(s) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR part 372. EPA has advised that when a percentage range is listed the midpoint may be used to fulfill reporting obligations.

Chemical Name	CAS#	%
Toluene	108-88-3	5 - 10
1,2,4-Trimethylbenzene	95-63-6	5 - 10
Manganese compounds	1313-13-9	5 - 10
ethylbenzene	100-41-4	0.1 - 1
Xylene (mixed isomers)	1330-20-7	0.1 - 1

WHMIS STATUS: Unless listed below, this product is not controlled under the Canadian Workplace Hazardous Materials Information System.

B2
D2A D2B

MATERIAL SAFETY DATA SHEET

STATE REPORTING

This MSDS is not prepared for distribution in California.

SECTION 16: ADDITIONAL INFORMATION

This Material Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

Prepared by: The Global Regulatory Department

Phone: 651-236-5842

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to Specialty Construction Brands, Inc. from its suppliers, and because Specialty Construction Brands, Inc. has no control over the conditions of handling and use, Specialty Construction Brands, Inc. makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and Specialty Construction Brands, Inc. assumes no responsibility for use or reliance thereon. It is the responsibility of the user of Specialty Construction Brands, Inc. products to comply with all applicable federal, state and local laws and regulations.