

# MATERIAL SAFETY DATA SHEET

## I. PRODUCT IDENTIFICATION

Name: Nomaco R-374 White latex  
Description: Rubber Insulation Coating  
EMERGENCY ONLY CONTACT: CHEM-TREC 1-800-424-9300

## II. HAZARDOUS INGREDIENTS

INGREDIENT:	CAS Number	PERCENT:	STEL	OSHA PEL	ACGIH TLV
Ester Alcohol	25265-77-4	< 5%		No Information	

# NOMACO

## R-374

Prepared 5/07

Made in USA for  
Nomaco K-Flex  
Youngsville NC, 27596

## III. PHYSICAL DATA

APPEARANCE AND COLOR: White liquid with a mild characteristic solvent odor. VAPOR DENSITY: (air=1) > 1. SOLUBILITY IN WATER: Yes. SPECIFIC GRAVITY: (water=1): 1.25. EVAPORATION RATE: slower than ether. VOC: 74 g/L calculated at 70° F, SCAQMD.

## IV. FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 240 F (CC). FLAMMABLE RANGE: LEL = 0.6%, UEL = 4.2% EXTINGUISHING MEDIA: Carbon dioxide, dry chemical, alcohol-type foam. SPECIAL FIRE FIGHTING PROCEDURES: Protect fire fighters from toxic products of combustion by wearing self-contained breathing apparatus. UNUSUAL FIRE AND EXPLOSION HAZARDS: Closed containers in a fire may rupture due to pressure build up. Use water to cool containers to prevent this.

## V. REACTIVITY DATA

STABILITY: Stable. INCOMPATIBILITY: Strong oxidizing agents. HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide and other toxic vapors and gases that are common to thermal degradation of organic compounds. HAZARDOUS POLYMERIZATION: Will not occur.

## VI. HEALTH HAZARD DATA/TOXICOLOGICAL PROPERTIES

PRIMARY ROUTES OF ENTRY: Inhalation and direct dermal exposure. TARGET ORGANS: Upper respiratory tract, skin and eyes. EFFECTS OF OVEREXPOSURE: Skin and Eyes: Excessive skin contact may cause drying and cracking of skin. Contact with eyes will cause irritation, blurred vision and redness. INHALATION: May cause irritation of respiratory tract, coughing and CNS effects, such as headache, dizziness, and nausea. INGESTION: May cause Gastrointestinal irritation, vomiting and diarrhea. CARCINOGENICITY: NTP: No. IARC Monographs: No. OSHA Regulated: No. MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Any condition generally aggravated by solvents; preexisting upper respiratory and lung disease such as, but not limited to, bronchitis, emphysema and asthma.

## VII. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Remove all sources of ignition. Ventilate area of spill or leak, if using mechanical ventilation, make sure that it is explosion proof or does not present an ignition source. For exposures above TLV, wear approved respiratory equipment. Contain spill and prevent it from entering sewer lines or waterways. Use absorbent to assist with the pick up of material. Scrape up adhesive and place in container. WASTE DISPOSAL METHOD: Dispose of container and any unused contents in accordance with federal, state and local waste disposal regulations. Do not flush unused contents or residue down drains. Do not reuse container.

## VIII. FIRST AID PROCEDURES

SKIN AND EYES: Flush any skin or eye contact with plenty of water for at least 15 minutes. Additionally with skin contact, wash skin thoroughly with soap and water. Refer to physician if irritation persists. INHALATION: Remove to fresh air if exposed to excess concentration of vapor. Seek medical attention if symptoms persist. INGESTION: Do not induce vomiting. Call Poison Control Center or physician for guidance.

## IX. SAFE HANDLING AND USE INFORMATION

Store in a dry and well ventilated area. Use natural cross ventilation, local (mechanical) pick up or general area (mechanical) ventilation to prevent accumulation of solvent vapors, keeping in mind that the ventilation pattern must remove the heavier than air solvent vapors from the lower levels of the work spaces. The ventilation should be sufficient to keep the solvent vapor concentration below the TLV. Empty containers may pose a risk, due to residual liquids. Containers should be grounded, during product transfer

## IX. SAFE HANDLING AND USE INFORMATION (Con't)

TLV. RESPIRATORY PROTECTION: With adequate ventilation, respiratory equipment should not be needed. If adequate ventilation is not afforded, wear respiratory equipment approved for organic vapors. SKIN AND EYE PROTECTION: During normal end product use, cotton or loop-pile gloves and safety glasses are recommended to prevent contact with this mastic product.

## X. SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Store in an area suitable for flammable mixtures. Recommended storage temperature is below 90°F. OTHER PRECAUTIONS: Vapors are flammable and are heavier than air. Prohibit smoking and eliminate all other sources of ignition, such as regular electric tools and appliances. Make sure that pilot lights on gas fired water heaters are extinguished. WORKSITE ENVIRONMENT: Initially there may be a potential adverse impact on indoor air quality within the general work area during installation. Therefore, you should advise the building manager or other appropriate person that; it will be necessary to establish and maintain adequate ventilation of the work area, without causing the entry of contaminants to other parts of the building. Persons who are sensitive to odors and/or chemicals should avoid the work area during this process.

## XI. REGULATORY INFORMATION

This product is not regulated by the DOT.

## HMIS (0=Minimal hazard; 4=severe hazard)

Health = 1 Flammability = 0 Reactivity = 0

## XII. PREPARATION INFORMATION

The information presented herein is supplied as a guide to those who handle or use this product. Safe work practices must be employed when working with any materials. It is important that the end user makes a determination regarding the adequacy of the safety procedures employed during the use of this product.

Prepared By: EH&S Specialist (919) 556-3475